Dane aktualne na dzień: 18-11-2026 22:21

Link do produktu: https://sklep.ps.com.pl/aruba-2530-24g-poe-switch-j9773a-limited-lifetime-warranty-p-94289.html

ARUBA 2530-24G-PoE+ Switch J9773A - Limited Lifetime Warranty



Cena brutto	**7 687,99 zł**
Cena netto	**6 250,40 zł**
Numer katalogowy	**NUHPESZ24POE002**
Kod producenta	**J9773A**
Kod EAN	**886112457778**
Rozmiar tablicy adresów MAC	**16000**
Prędkość przekazywania (Mpps)	**41.6**
Liczba portów 10/100 Mbps	**Brak**
Liczba portów PoE (PoE + PoE+)	**24**
Liczba portów SFP+	**Brak**
Liczba grup VLAN (tylko mng i smart)	**512**
Liczba portów SFP	**4**
Liczba portów 10Gb	**Brak**
Zastosowanie (switche)	**Średnie i duże firmy (powyżej 16 portów)**
Wentylator (switche)	**Nie**
Warstwa przełączania (switche)	**L2**
Tryb przekazywania	**Store-and-forward**
Port konsoli	**Tak**
Klasa przełącznika	**Zarządzalny**
Przepustowość (switche Gbps)	**56**
Liczba portów 10/100/1000 Mbps	**24**
Architektura sieci (switche)	**GigabitEthernet**
Typ obudowy	**Rack (Switche/UPS)**
Zarządzanie, monitorowanie, konfiguracja	**- Virtual stacking — provides single IP address management for up to 16 switches- sFlow (RFC 3176) — delivers wire-speed traffic accounting and monitoring configured by SNMP and CLI with three terminal encrypted receivers- IEEE 802.1AB Link La**
Pobór mocy	**247**
Bezpieczeństwo	**- Access control lists (ACLs) — accommodates IPv4/IPv6 port and VLAN-based ACLs (IPv6 ACL is supported only on Gigabit**

	Ethernet and 48-port models)- Source-port filtering — allows only specified ports to communicate with each other- RADIUS/TAC
Waga	**3.95**
Wymiary	**44.3 x 33.02 x 4.45 cm**
VLAN	**VLANs — provides support for 512 VLANs and 4,094 VLAN IDs**
Rozmiar ramki Jumbo	**9**
QoS	**- Traffic prioritization (IEEE 802.1p) — allows real-time traffic classification with support for eight priority levels mapped to either two or four queues; uses weighted deficit round robin (WDRR) or strict priority (SP)- Simplified QoS configurati**
Funkcje L2	**- VLANs — provides support for 512 VLANs and 4,094 VLAN IDs- Jumbo packet support — supports up to 9220-byte frame size to improve the performance of large data transfers; 8- and 24-port Fast Ethernet models automatically support up to 2000-by**
Obsługa ramek Jumbo	**Tak**
Bufor pakietów	**1.5**
Liczba portów PoE+	**Brak**
Liczba portów COMBO	**Brak**

Opis produktu