Dane aktualne na dzień: 18-11-2026 21:28

Link do produktu: https://sklep.ps.com.pl/aruba-2530-8g-switch-j9777a-limited-lifetime-warranty-p-38700.html

ARUBA 2530-8G Switch J9777A - Limited Lifetime Warranty



Cena brutto	**3 716,99 zł**
Cena netto	**3 021,94 zł**
Numer katalogowy	**NUHPESZ8P000001**
Kod producenta	**J9777A**
Kod EAN	**886112458713**
Rozmiar tablicy adresów MAC	**16000**
Prędkość przekazywania (Mpps)	**14.8**
Liczba portów 10/100 Mbps	**Brak**
Liczba portów PoE (PoE + PoE+)	**Brak**
Liczba portów SFP+	**Brak**
Liczba grup VLAN (tylko mng i smart)	**512**
Liczba portów SFP	**Brak**
Liczba portów 10Gb	**Brak**
Zastosowanie (switche)	**Średnie i duże firmy (powyżej 16 portów)**
Wentylator (switche)	**Nie**
Warstwa przełączania (switche)	**L2**
Tryb przekazywania	**Store-and-forward**
Port konsoli	**Tak**
Klasa przełącznika	**Zarządzalny**
Przepustowość (switche Gbps)	**20**
Liczba portów 10/100/1000 Mbps	**8**
Architektura sieci (switche)	**GigabitEthernet**
Typ obudowy	**Rack (Switche/UPS)**
Zarządzanie, monitorowanie, konfiguracja	**- Virtual stacking — provides single IP address management for up to 16 switches- sFlow (RFC 3176) — delivers wire-speed traffic accounting and monitoring configured by SNMP and CLI with three terminal encrypted receivers- IEEE 802.1AB Link La**
Pobór mocy	**18.6**
Bezpieczeństwo	**- Access control lists (ACLs) — accommodates IPv4/IPv6 port and VLAN-based ACLs (IPv6 ACL is supported only on Gigabit**

	Ethernet and 48-port models)- Source-port filtering — allows only specified ports to communicate with each other- RADIUS/TAC
Waga	**0.91**
Wymiary	**25.4 x 15.95 x 4.45 cm**
VLAN	**VLANs — provides support for 512 VLANs and 4,094 VLAN IDs**
Rozmiar ramki Jumbo	**9**
QoS	**- Traffic prioritization (IEEE 802.1p) — allows real-time traffic classification with support for eight priority levels mapped to either two or four queues; uses weighted deficit round robin (WDRR) or strict priority (SP)- Simplified QoS configurati**
Funkcje L2	**- VLANs — provides support for 512 VLANs and 4,094 VLAN IDs- Jumbo packet support — supports up to 9220-byte frame size to improve the performance of large data transfers; 8- and 24-port Fast Ethernet models automatically support up to 2000-by**
Obsługa ramek Jumbo	**Tak**
Bufor pakietów	**1.5**
Liczba portów PoE+	**Brak**
Liczba portów COMBO	**2**

Opis produktu