Dane aktualne na dzień: 18-11-2026 19:08

Link do produktu: https://sklep.ps.com.pl/dgs-1510-28p-poe-switch-24xgb-2sfp-2xsfp-p-38502.html

DGS-1510-28P PoE Switch 24xGb+2SFP+2xSFP+



Cena brutto	**3 196,99 zł**
Cena netto	**2 599,18 zł**
Numer katalogowy	**NUDLISS28DGS002**
Kod producenta	**DGS-1510-28P**
Kod EAN	**790069399473**
Funkcje L3	**- ARP - 256 Static ARP - Supports Gratuitous ARP - IPv6 Neighbour Discovery (ND) - 16 IP interfaces- Default Routing - Static Routing - 64 IPv4 Static Route Entries - 32 IPv6 Static Route Entries**
Wymiary	**440 x 250 x 44 mm**
VLAN	**- 802.1Q Tagged VLAN - 4K VLAN Groups - Configurable VID: 0~4094 - Asymmetric VLAN - Auto Voice VLAN - Auto Surveillance VLAN**
Rozmiar ramki Jumbo	**9**
QoS	**- 802.1p Quality of Service - Queue Handling - Strict - Weighted Round Robin (WRR) - 8 queues per port - Bandwidth Control - Port-based (Ingress/Egress, min. granularity for 10/100/1000Base-T ports is 64 Kb/s) - CoS base**
Funkcje L2	**- MAC Address Table: 16K - Flow Control - 802.3x Flow Control - HOL Blocking Prevention - Jumbo Frame up to 9000 Bytes - IGMP Snooping - IGMP v1/v2 Snooping - IGMP v3 awareness - Supports 512 IGMP groups - Supp**
Obsługa ramek Jumbo	**Tak**
Bufor pakietów	**1.5**
Liczba portów QSFP+	**Brak**
Liczba portów PoE+	**Brak**
Liczba portów COMBO	**Brak**
Rozmiar tablicy adresów MAC	**16000**
Prędkość przekazywania (Mpps)	**68.45**
Liczba portów 10/100 Mbps	**Brak**
Liczba portów PoE (PoE + PoE+)	**24**

Liczba portów SFP+	**2**
Liczba grup VLAN (tylko mng i smart)	**256**
Liczba portów SFP	**2**
Zastosowanie (switche)	**Średnie i duże firmy (powyżej 16 portów)**
Zasilacz (switche)	**Wewnętrzny**
Wentylator (switche)	**Tak**
Warstwa przełączania (switche)	**L2**
Port konsoli	**Tak**
Klasa przełącznika	**SMART**
Przepustowość (switche Gbps)	**92**
Liczba portów 10/100/1000 Mbps	**24**
Architektura sieci (switche)	**GigabitEthernet**
Typ obudowy	**Rack (Switche/UPS)**
Zarządzanie, monitorowanie, konfiguracja	**- CLI - Telnet Server - TFTP Client - IPv6 Neighbor Discovery - Configurable MDI/MDIX - SNMP - Supports v1, v2c, v3 - SNMP Trap - System Log - Max. 10,000 log entries - DHCP Client - D-Link Network As**
Pobór mocy	**238.7**
Bezpieczeństwo	**- Port Security - Supports up to 128 MAC addresses per port - Broadcast/Multicast/Unicast Storm Control - Dynamic ARP Inspection - Static MAC - D-Link Safeguard Engine - DHCP Server Screening - ARP Spoofing Prevention&#1**
Zasilanie	**100 to 240 VAC, 50 to 60Hz**
Waga	**2.54**

Opis produktu