Dane aktualne na dzień: 18-11-2026 20:28

Link do produktu: https://sklep.ps.com.pl/przelacznik-dxs-3400-24sc-24xsfp-4x10gb-p-264572.html

Przełącznik DXS-3400-24SC 24xSFP+ 4x10Gb



Cena brutto	**27 612,99 zł**
Cena netto	**22 449,59 zł**
Numer katalogowy	**NUDLISZ24000010**
Kod producenta	**DXS-3400-24SC**
Kod EAN	**790069423604**
Możliwość łączenia w stos	**Tak**
Liczba portów 10Gb	**24**
Zastosowanie (switche)	**Średnie i duże firmy (powyżej 16 portów)**
Zasilacz (switche)	**Wewnętrzny**
Wentylator (switche)	**Tak**
Warstwa przełączania (switche)	**L3**
Tryb przekazywania	**Store-and-forward**
Port konsoli	**Tak**
Klasa przełącznika	**Zarządzalny**
Przepustowość (switche Gbps)	**480**
Architektura sieci (switche)	**GigabitEthernet**
Typ obudowy	**Rack (Switche/UPS)**
Zarządzanie, monitorowanie, konfiguracja	**Web-based GUI CLI Telnet Server Telnet Client TFTP Client FTP Client Secure FTP (SFTP) Server Traffic Monitoring SNMP Supports v1/v2c/v3 SNMP Trap System Log DHCP Client DHCP Server DHCP Relay options 60, 61, 82 Multiple Images Multiple Configurations Fl**
Pobór mocy	**118.6**
Obsługiwane protokoły i standardy	**MIB Structure: RFC1065, RFC1066, RFC1155, RFC1156, RFC2578 Concise MIB Definitions: RFC1212 MIBII: RFC1213 MIB Traps Convention: RFC1215 Bridge MIB: RFC1493, RFC4188 SNMP MIB: RFC1157, RFC2571, RFC2572, RFC2573, RFC2574, RFC2575, RFC2576 SNMPv2 MIB: RFC14**
Bezpieczeństwo	**Port Security Supports up to 12K MAC addresses per port/system Broadcast/Multicast/Unicast**

	Storm Control D-Link Safeguard Engine DHCP Server Screening IP-MAC-Port Binding Dynamic ARP Inspection IP Source Guard DHCP Snooping IPv6 Snooping DHCPv6 Guard IPv
Zasilanie	**120 - 240 V AC Sieciowe**
Waga	**5.1**
Wymiary	**441 x 44 x 380 mm**
Funkcje L3	**ARP 512 Static ARP Supports Gratuitous ARP ARP Proxy IP Interface Supports 256 interfaces Loopback Interface IPv6 Neighbor Discovery (ND) UDP Helper IPv6 Tunneling Static ISATAP GRE 6to4 IGMP Proxy Reporting VRRP v2/v3**
VLAN	**802.1Q 802.1v Double VLAN (Q-in-Q) Port-based Q-in-Q Selective Q-in-Q Port-based VLAN MAC-based VLAN Subnet-based VLAN Private VLAN VLAN Group Max. 4K static VLAN groups Max. 4094 VIDs ISM VLAN (Multicast VLAN) Voice VLAN Auto Surveillance VLAN VLAN Tru**
Rozmiar ramki Jumbo	**12**
QoS	**802.1p Quality of Service 8 queues per port QoS based on 802.1p Priority Queues DSCP IP address MAC address VLAN IPv6 Traffic Class IPv6 Flow Label TCP/UDP port Switch Port Ether Type ToS/IP Preference Protocol Type Congestion Control WRED Queue Handlin**
Funkcje L2	**MAC Address Table Up to 48K entries Flow Control 802.3x Flow Control when using Full Duplex Back Pressure when using Half Duplex HOL Blocking Prevention Spanning Tree Protocol 802.1D STP 802.1w RSTP 802.1s MSTP Root Guard Loop Guard Jumbo Frame Up to 1**
Bufor pamięci (switche)	**4**
Obsługa ramek Jumbo	**Tak**
Liczba portów COMBO	**4**
Rozmiar tablicy adresów MAC	**48000**
Prędkość przekazywania (Mpps)	**357.12**

Opis produktu

Przełączniki serii DXS-3400 zawierają 20 x 10GBASE-T lub 20 x 10G SFP + i 4 porty combo 10 GHz-T / SFP +, dzięki czemu nadają się do zastosowania w centrach danych i dystrybucji.