Dane aktualne na dzień: 18-11-2026 21:54

Link do produktu: https://sklep.ps.com.pl/przelacznik-smart-dgs-1510-52xmp-48xge-24xpoe-370w-4sfp-p-38504.html

Przełącznik Smart DGS-1510-52XMP 48xGE (24xPoE - 370W) 4SFP+



Cena brutto	**6 333,99 zł**
Cena netto	**5 149,59 zł**
Numer katalogowy	**NUDLISS48000003**
Kod producenta	**DGS-1510-52XMP**
Kod EAN	**790069434303**
Zasilacz (switche)	**Wewnętrzny**
Wentylator (switche)	**Tak**
Warstwa przełączania (switche)	**L2**
Tryb przekazywania	**Store-and-forward**
Klasa przełącznika	**SMART**
Przepustowość (switche Gbps)	**176**
Liczba portów 10/100/1000 Mbps	**48**
Architektura sieci (switche)	**GigabitEthernet**
Typ obudowy	**Rack (Switche/UPS)**
Zarządzanie, monitorowanie, konfiguracja	**Command Line Interface (CLI) Telnet Server TFTP Client IPv6 Neighbor Discovery Configurable MDI/MDIX SNMP Supports v1, v2c, v3 SNMP Trap System Log Max. 10,000 log entries Debug command Multiple images Surveillance mode DHCP Client D-Link Ne**
Pobór mocy	**40.1**
Obsługiwane protokoły i standardy	**IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3ab 1000BASE-T Gigabit Ethernet, 802.3ae 10 GbE, IEEE 802.3x Flow Control for Full-Duplex Mode, Auto-negotiation**
Bezpieczeństwo	**Port Security Supports up to 128 MAC addresses per port Broadcast/Multicast/Unicast Storm Control Dynamic ARP Inspection D-Link Safeguard Engine DHCP Server Screening ARP Spoofing Prevention Max. 64 entries SSH Supports v2 Supports IPv4/IPv6 BPDU**
Zasilanie	**Zasilacz 100 to 240 VAC 50/60 Hz**
Waga	**5.41**

Wymiary	**440 x 308 x 44 mm**
Pozostałe parametry	**Certyfikaty: CE, FCC, C-Tick, VCCI, BSMI, CCC**
VLAN	**802.1Q Tagged VLAN 4K VLAN Groups Configurable VID: 0~4094 GVRP Asymmetric VLAN Auto Voice VLAN Auto Surveillance VLAN 2.1 MAC-based VLAN Protocol-based VLAN**
QoS	**CoS based on 802.1p priority VLAN MAC address Ether type IP address DSCP Protocol type TCP/UDP port number DSCP of IPv6 Traffic Class IPv6 flow label 802.1p Quality of Service Queue Handling Strict Priority Queue (SPQ) Weighted Round Robin (**
Bufor pakietów	**3**
Rozmiar tablicy adresów MAC	**16.384**
Prędkość przekazywania (Mpps)	**130.95**
Liczba portów PoE (PoE + PoE+)	**48**
Liczba portów SFP+	**4**
Możliwość łączenia w stos	**Tak**
Zastosowanie (switche)	**Średnie i duże firmy (powyżej 16 portów)**

Opis produktu

Cechy główne:

- Zarządzanie i bezpieczeństwo L2 z funkcjami L3
- Wiersz poleceń CLI, port konsoli oraz graficzny interfejs użytkownika Web
- 10G SFP+ stakowanie fizyczne
- Trasy statyczne i MSTP
- Opcja PoE (Power over Ethernet) z budżetem mocy do 740W2
- Dożywotnia gwarancja Lifetime-Limited po rejestracji