Dane aktualne na dzień: 18-11-2026 17:31

Link do produktu: https://sklep.ps.com.pl/smart-switch-48x10gb-xs748t-100nes-p-309308.html

SMART Switch 48x10Gb XS748T-100NES



Cena brutto	**21 900,99 zł**
Cena netto	**17 805,68 zł**
Numer katalogowy	**NUNTGSS48000007**
Kod producenta	**XS748T-100NES**
Kod EAN	**606449112382**
Zastosowanie (switche)	**Średnie i duże firmy (powyżej 16 portów)**
Zasilacz (switche)	**Wewnętrzny**
Wentylator (switche)	**Tak**
Warstwa przełączania (switche)	**L2**
Tryb przekazywania	**Store-and-forward**
Klasa przełącznika	**SMART**
Liczba portów 10/100/1000 Mbps	**44**
Czas pracy pomiędzy awariami (MTBF)	**483.808**
Architektura sieci (switche)	**GigabitEthernet**
Typ obudowy	**Rack (Switche/UPS)**
Zarządzanie, monitorowanie, konfiguracja	**- Password management- Configurable management VLAN- Admin access control via RADIUS and TACACS+- IPv6 management- SNTP client over UDP port 123- SNMP v1/v2c- SNMP v3 with multiple IP addresses- RMON group 1,2,3,9- Port mirroring- Many-to-one port mirrori**
Pobór mocy	**262.8**
Obsługiwane protokoły i standardy	**- IEEE 802.1ab- IEEE 802.1d- IEEE 802.1p- IEEE 802.1q- IEEE 802.1s- IEEE 802.1w- IEEE 802.1x- IEEE 802.3- IEEE 802.3ab- IEEE 802.3ad- IEEE 802.3ae- IEEE 802.3az- IEEE 802.3i- IEEE 802.3u- IEEE 802.3x- IEEE 802.3z**
Bezpieczeństwo	**- IEEE 802.1X- RADIUS accounting- Access Control Lists (ACLs): L2 / L3 / L4- MAC lockdown- MAC lockdown by the number of MACs- Control MAC # Dynamic learned entries: 600- Control MAC # static entries: XS708T/XS716T: 20 ----- XS728T/XS748T: 600- IEEE 802.1**

Zasilanie	**Internal 100-240VAC 50-60Hz**
Waga	**6.25**
Wymiary	**440 x 310 x 43 mm**
Funkcje L3	**- IPv4 static routes: XS708T/XS716T: 32 ----- XS728T/XS748T: 64- IPv6 static routes: XS708T/XS716T: 32 ----- XS728T/XS748T: 64- Host ARP table: XS708T/XS716T: 738 entries ----- XS728T/XS748T: 1024 entries- ICMP Router Discovery Protocol (IRDP): XS708T/XS7**
VLAN	**- Number of VLANs: XS708T/XS716T: 256 ----- XS728T/XS748T: 512- IEEE 802.1Q VLAN Tagging- IP-based VLANs- MAC-based VLANs- Auto-VoIP based on protocols (SIP, H323 and SCCP)- Auto-Voice VLAN based on OUI bytes (default database and user-based OUIs) in the**
QoS	**- Port-based rate limiting: XS708T/XS716T: Egress only ----- XS728T/XS748T: Ingress and egress- Port-based QoS- Support for IPv6 fields- DiffServ QoS- IEEE 802.1p COS- Destination MAC and IP- IPv4 and IPv6 DSCP- IPv4 and IPv6 ToS- TCP/UDP-based- Weighted**
Funkcje L2	**- Broadcast, multicast, unknown unicast storm control- IEEE 802.3ad - LAGs (LACP)- IEEE 802.3x (full duplex and flow control)- IEEE 802.1D Spanning Tree Protocol- IEEE 802.1w Rapid Spanning Tree Protocol- IEEE 802.1s Multiple Spanning Tree Protocol**
Bufor pakietów	**3**
Rozmiar tablicy adresów MAC	**16000**
Liczba portów SFP+	**4**
Liczba grup VLAN (tylko mng i smart)	**512**
Możliwość łączenia w stos	**Tak**

Opis produktu