Dane aktualne na dzień: 18-11-2026 21:54

Link do produktu: https://sklep.ps.com.pl/switch-xgs4600-32f-24xsfp-4xgb-sfp-4x10gb-sfp-p-39679.html

# Switch XGS4600-32F 24xSFP 4xGb/SFP 4x10Gb SFP+



| | |
|---|---|
| Cena brutto | **9 868,99 zł** |
| Cena netto | **8 023,57 zł** |
| Numer katalogowy | **NUZYXSZ32000002** |
| Kod producenta | **XGS4600-32F-ZZ0102F** |
| Kod EAN | **4718937590575** |
| Uwaga | **CE+WEEE** |
| QoS | **- Two Rate Three Color Marker (trTCM)- CIR/PIR bandwidth control- Port-based egress traffic shaping- Broadcast storm control- IEEE 802.1p with 8 priority queues per port- WFR, WRR, SPQ scheduling algorithms- DSCP/DSCP to 802.1p priority mapping- IGMP/IGMP** |
| Bufor pakietów | **4** |
| Liczba portów QSFP+ | **Brak** |
| Liczba portów PoE+ | **Brak** |
| Liczba portów COMBO | **4** |
| Rozmiar tablicy adresów MAC | **32000** |
| Prędkość przekazywania (Mpps) | **101.1** |
| Liczba portów 10/100 Mbps | **Brak** |
| Liczba portów PoE (PoE + PoE+) | **Brak** |
| Liczba portów SFP+ | **4** |
| Liczba portów SFP | **24** |
| Liczba portów 10Gb | **4** |
| Zastosowanie (switche) | **Średnie i duże firmy (powyżej 16 portów)** |
| Warstwa przełączania (switche) | **L3** |
| Tryb przekazywania | **Store-and-forward** |
| Port konsoli | **Tak** |
| Klasa przełącznika | **Zarządzalny** |
| Przepustowość (switche Gbps) | **136** |
| Architektura sieci (switche) | **GigabitEthernet** |
| Typ obudowy | **Rack (Switche/UPS)** |
| Zarządzanie, monitorowanie, konfiguracja | **- Zyxel iStacking™, up to 24 switches managed by a single IP** |

| | |
|---|---|
| | **address- Physical stacking up to 4 switches- Web-based management- Telnet- SSH- SNMP v1, v2c, v3- RS-232c local console- IP management: static IP or DHCP-assigned IP- Four RMON groups 1, 2** |
| Pobór mocy | **47** |
| Obsługiwane protokoły i standardy | **- IEEE 802.3 10Base-T Ethernet- IEEE 802.3u 100Base-Tx Ethernet- IEEE 802.3ab 1000Base-T Ethernet- IEEE 802.3z 1000 Base-X- IEEE 802.3x flow control- IEEE 802.3az EEE support- IEEE 802.1p CoS support- IEEE 802.1D Spanning Tree Protocol (STP)- IEEE 802.1w** |
| Bezpieczeństwo | **- IEEE 802.1Q tag-based and port-based VLAN- GVRP automatic VLAN member registration- 1 K static VLANs and up to 4 K dynamic VLANs- Full range 4 K PVID support- Port-based VLAN and VLAN isolation- IP classification VLAN- VLAN counter- VLAN search- VLAN tr** |
| Zasilanie | **100 - 240 V AC, 50/60 Hz** |
| Waga | **3.96** |
| Wymiary | **441 x 270 x 44 mm** |

## Opis produktu